

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version	Revision Date:	MSDS Number:	Date of last issue: -
1. 0	09/05/2014	540786-00001	Date of first issue: 09/05/2014

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Product code : 000000000002893886

Chemical nature : Silicone elastomer

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Disposal considerations : (989) 496-6315

Recommended use of the chemical and restrictions on use

Recommended use : Electrical industry and electronics

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	liquid
Color	yellow
Odor	slight alcoholic
Hazard Summary	No known physical or health hazards.

OSHA Regulatory status : This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Potential Health Effects

Inhalation : No significant effects expected from a single short-term exposure.

Skin : No significant irritation expected from a single short-term exposure.

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version 1. 0	Revision Date: 09/05/2014	MSDS Number: 540786-00001	Date of last issue: - Date of first issue: 09/05/2014
-----------------	------------------------------	------------------------------	--

Eyes : No significant irritation expected from a single exposure.

Ingestion : No significant effects expected from a single short-term exposure.

Aggravated Medical Condition : None known.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone elastomer

Hazardous ingredients

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version	Revision Date:	MSDS Number:	Date of last issue: -
1. 0	09/05/2014	540786-00001	Date of first issue: 09/05/2014

Rinse mouth thoroughly with water.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Dry chemical
Carbon dioxide (CO₂)

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version 1.0	Revision Date: 09/05/2014	MSDS Number: 540786-00001	Date of last issue: - Date of first issue: 09/05/2014
----------------	------------------------------	------------------------------	--

Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types: Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Contains no substances with occupational exposure limit values.

Engineering measures : Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection : Wash hands before breaks and at the end of workday.

Remarks

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version	Revision Date:	MSDS Number:	Date of last issue: -
1. 0	09/05/2014	540786-00001	Date of first issue: 09/05/2014

Eye protection	: Wear the following personal protective equipment: Safety glasses
Skin and body protection	: Skin should be washed after contact.
Hygiene measures	: Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: yellow
Odor	: slight alcoholic
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 65 °C
Flash point	: > 100 °C Method: Seta closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version 1.0	Revision Date: 09/05/2014	MSDS Number: 540786-00001	Date of last issue: - Date of first issue: 09/05/2014
----------------	------------------------------	------------------------------	--

Relative vapor density	: No data available
Relative density	: 0.98
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity Viscosity, kinematic	: 450 cSt
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products Thermal decomposition	: Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	: Inhalation
---------------------------------	--------------

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version 1.0	Revision Date: 09/05/2014	MSDS Number: 540786-00001	Date of last issue: - Date of first issue: 09/05/2014
----------------	------------------------------	------------------------------	--

exposure	Skin contact
	Ingestion
	Eye contact

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version	Revision Date:	MSDS Number:	Date of last issue: -
1. 0	09/05/2014	540786-00001	Date of first issue: 09/05/2014

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

OSHA Hazards : No OSHA Hazards

EPCRA - Emergency Planning and Community Right-to-Know**CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylbenzene	100-41-4	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version 1.0	Revision Date: 09/05/2014	MSDS Number: 540786-00001	Date of last issue: - Date of first issue: 09/05/2014
----------------	------------------------------	------------------------------	--

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Pennsylvania Right To Know**

Dimethyl Siloxane, Dimethylvinylsiloxo-terminated	68083-19-2	90 - 100 %
---	------------	------------

New Jersey Right To Know

Dimethyl Siloxane, Dimethylvinylsiloxo-terminated	68083-19-2	90 - 100 %
Silicate	Proprietary Ingredient	1 - 5 %

California Prop 65

Ethylbenzene	WARNING! This product contains a chemical known in the State of California to cause cancer. 100-41-4
--------------	---

The ingredients of this product are reported in the following inventories:

KECI : One or more ingredients are not listed or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

DSL : This product contains one or more substances which are not on the Canadian Domestic Substances List (DSL). Import of this product into Canada has volume limitations. For volume limits please consult Dow Corning Regulatory Compliance.

REACH : Consult your local Dow Corning office.

AICS : Consult your local Dow Corning office.

IECSC : Consult your local Dow Corning office.

ENCS/ISHL : Some components are not listed or not identified on ENCS/ISHL.

PICCS : Consult your local Dow Corning office.

DOW CORNING(R) 3-4207 DIELECTRIC TOUGH GEL KIT (PART A information is be

Version 1. 0	Revision Date: 09/05/2014	MSDS Number: 540786-00001	Date of last issue: - Date of first issue: 09/05/2014
-----------------	------------------------------	------------------------------	--


NZIoC : All ingredients listed or exempt.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

Registration: Trade Secret

Component	Registration number
Silicate	NJ TSRN 14962700-5376P

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8