

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686

24 Hour Emergency Telephone: (989) 496-5900

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 01595725

Revision Date: 2014/06/25

Generic Description: Silicone elastomer

Physical Form: Paste

Color: Gray

Odor: Slight odor

NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS**Acute Effects**

Eye: Direct contact may cause temporary redness and discomfort.

Skin: No significant irritation expected from a single short-term exposure.

Inhalation: No significant effects expected from a single short-term exposure.

Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged exposure may cause irritation.

Inhalation: No known applicable information.

Oral: Repeated ingestion or swallowing large amounts may injure internally.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

None present. This is not a hazardous material as defined in the OSHA Hazard Communication Standard.

4. FIRST AID MEASURES

Eye:	If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. Obtain medical attention.
Skin:	No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Inhalation:	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Oral:	If irritation or discomfort occur, obtain medical advice.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

5. FIRE FIGHTING MEASURES

Flash Point:	Not applicable.
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire Hazards:	None.

6. ACCIDENTAL RELEASE MEASURES

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Traces of benzene (carcinogen) may form if heated in air above 300°F (149°C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements. Avoid eye contact. Avoid skin contact. Do not take internally.

Use reasonable care and store away from oxidizing materials. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Component Exposure Limits**

There are no components with workplace exposure limits.

Engineering Controls

Local Ventilation: None should be needed.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.
Skin: Washing at mealtime and end of shift is adequate.

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Inhalation: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

Personal Protective Equipment for Spills

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Inhalation/Suitable Respirator: No respiratory protection should be needed.

Precautionary Measures: Avoid eye contact. Avoid skin contact. Do not take internally. Use reasonable care.

Comments: Traces of benzene (carcinogen) may form if heated in air above 300°F (149°C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste
 Color: Gray
 Odor: Slight odor
 Specific Gravity @ 25°C: 1.52
 Viscosity: Not determined.
 Freezing/Melting Point: Not determined.
 Boiling Point: Not determined.
 Vapor Pressure @ 25°C: Not determined.
 Vapor Density: Not determined.
 Solubility in Water: Not determined.
 pH: Not determined.
 Volatile Content: Not determined.
 Flash Point: Not applicable.
 Autoignition Temperature: Not determined.
 Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.
Conditions to Avoid:	None.
Materials to Avoid:	Oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Formaldehyde. Silicon dioxide. Quartz.

11. TOXICOLOGICAL INFORMATIONSpecial Hazard Information on Components

No known applicable information.

12. ECOLOGICAL INFORMATIONEnvironmental Fate and Distribution

Air:	This product is a solid consisting of a high molecular weight silicone polymer and other solid materials. Unless milled to produce a dust or particles, it is unlikely to give rise to atmospheric contamination.
Water:	This product is a solid which is completely insoluble in water. As the specific gravity is >1, it will sink to the bottom of the water course.
Soil:	This product will enter the terrestrial environment if, as a component of municipal or industrial solid waste the product is landfilled. It is unlikely that further significant transformation of the product will occur.
Degradation:	High molecular weight polymer which is amenable to recycling. The product is not biodegradable. The product is removed >80% during the sewage treatment process.

Environmental Effects

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

Toxicity to Water Organisms: This product has low water solubility and should not present a risk to aquatic organisms.

Toxicity to Soil Organisms: This product is a solid and does not contain significant concentrations of water soluble constituents that may be leached from the product. It is therefore not likely to present a danger to terrestrial organisms.

Bioaccumulation: This product is a solid which is not soluble in water and if ingested will not be absorbed.

Fate and Effects in Waste Water Treatment Plants

This product is a solid rubber type material which is unlikely to have any adverse effect on bacteria.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION**DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings**Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):

Acute: No
Chronic: No
Fire: No
Pressure: No
Reactive: No

Section 313 Toxic Chemicals (40 CFR 372):

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
67-56-1	<0.1000	Methyl alcohol	Developmental toxin.
108-88-3	<0.0100	Toluene	Developmental toxin.

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate

DOW CORNING(R) 795 SILICONE BUILDING SEALANT, GRAY

70131-67-8	30.0 - 50.0	Dimethyl siloxane, hydroxy-terminated
63148-62-9	7.0 - 13.0	Polydimethylsiloxane
112945-52-5	3.0 - 7.0	Amorphous fumed silica
80801-30-5	1.0 - 5.0	Phenylmethyl siloxane, hydroxy-terminated
14808-60-7	<1.0	Quartz
13463-67-7	<=0.3	Titanium dioxide

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate
70131-67-8	30.0 - 50.0	Dimethyl siloxane, hydroxy-terminated
63148-62-9	7.0 - 13.0	Polydimethylsiloxane
112945-52-5	3.0 - 7.0	Amorphous fumed silica

16. OTHER INFORMATION

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark