



# XIAMETER(R) Material Safety Data Sheet

Page: 1 of 8

Version: 1.1

Revision Date: 2013/06/07

## XIAMETER(R) RTV-3010-S CATALYST

### 1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Corporation  
South Saginaw Road  
Midland, Michigan 48686

**24 Hour Emergency Telephone: (989) 496-5900**

Customer Service: (989) 496-4430

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 04107697

Revision Date: 2013/06/07

Generic Description: Silicone  
Physical Form: Viscous Liquid  
Color: Light blue  
Odor: Fatty odor

NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

### 2. HAZARDS IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS

##### Acute Effects

Eye: Direct contact may cause temporary redness and discomfort.

Skin: No significant irritation expected from a single short-term exposure.

Inhalation: Irritates respiratory passages very slightly.

Oral: Low ingestion hazard in normal use.

##### Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged exposure may cause irritation.

Inhalation: No known applicable information.

Oral: Overexposure by ingestion may injure the following organ(s): Thymus. Kidneys. Nervous system.

##### Other Health Effects

This product contains a chemical(s) that has the following effect(s):

Developmental Toxicity  
Carcinogenicity

See Section 11 for specific details.

##### Signs and Symptoms of Overexposure

## XIAMETER(R) RTV-3010-S CATALYST

No known applicable information.

### **Medical Conditions Aggravated by Exposure**

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
68928-76-7	5.0 - 10.0	Dimethylbis[(1-oxoneodecyl)oxy]stannane
1345-16-0	<0.1	C.I. Pigment Blue 28

The above components are hazardous as defined in 29 CFR 1910.1200.

### **4. FIRST AID MEASURES**

Eye:	If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. Obtain medical attention.
Skin:	No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Inhalation:	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Oral:	If irritation or discomfort occur, obtain medical advice.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

### **5. FIRE FIGHTING MEASURES**

Flash Point:	> 214 °F / > 101.1 °C (Closed Cup)
Autoignition Temperature:	> 212 °F / > 100 °C
Flammability Limits in Air:	Not determined.
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO <sub>2</sub> ), dry chemical or water spray. Water can be used to cool fire exposed containers.

## XIAMETER(R) RTV-3010-S CATALYST

**Fire Fighting Measures:** Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

**Unusual Fire Hazards:** None.

### 6. ACCIDENTAL RELEASE MEASURES

**Containment/Clean up:** Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbant. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

**Note:** See Section 8 for Personal Protective Equipment for Spills.

### 7. HANDLING AND STORAGE

Use with adequate ventilation. Avoid eye contact. Avoid skin contact. Do not take internally.

Use reasonable care and store away from oxidizing materials.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Component Exposure Limits

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]stannane	Observe organic tin compounds limits. OSHA PEL and ACGIH TLV-skin: TWA 0.1 mg/m <sup>3</sup> ; ACGIH STEL 0.2 mg/m <sup>3</sup> .
1345-16-0	C.I. Pigment Blue 28	Observe particulate limits. OSHA PEL: TWA 15 mg/m <sup>3</sup> total dust, 5 mg/m <sup>3</sup> respirable fraction. ACGIH TLV: TWA 10 mg/m <sup>3</sup> inhalable particulate, 3 mg/m <sup>3</sup> respirable particulate.

#### Engineering Controls

**Local Ventilation:** None should be needed.

## XIAMETER(R) RTV-3010-S CATALYST

General Ventilation: Recommended.

### **Personal Protective Equipment for Routine Handling**

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Inhalation: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

### **Personal Protective Equipment for Spills**

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Inhalation/Suitable Respirator: No respiratory protection should be needed.

Precautionary Measures: Avoid eye contact. Avoid skin contact. Do not take internally. Use reasonable care.

Comments: When heated to temperatures above 180°C (356°F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Viscous Liquid

Color: Light blue

Odor: Fatty odor

Specific Gravity @ 25°C: 1.1

Viscosity: 10,000 mPa s

Freezing/Melting Point: Not determined.

Boiling Point: > 65 °C

Vapor Pressure @ 25°C: No data available

Vapor Density: Not determined.

Solubility in Water: Not determined.

## XIAMETER(R) RTV-3010-S CATALYST

pH: Not determined.  
Volatile Content: Not determined.  
Flash Point: > 214 °F / > 101.1 °C (Closed Cup)  
Autoignition Temperature: > 212 °F / > 100 °C  
Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications.

### 10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

#### Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde. Metal oxides. Nitrogen oxides.

### 11. TOXICOLOGICAL INFORMATION

#### Special Hazard Information on Components

##### **Carcinogens**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
1345-16-0	<0.1	C.I. Pigment Blue 28	IARC Group 2B - Possibly Carcinogenic to Humans. Cobalt compound.

##### **Developmental Toxicity**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
68928-76-7	5.0 - 10.0	Dimethylbis[(1-oxoneodecyl)oxy]stannane	Evidence of teratogenicity (birth defects) in laboratory animals at maternally toxic doses.

### 12. ECOLOGICAL INFORMATION

#### Environmental Fate and Distribution

## XIAMETER(R) RTV-3010-S CATALYST

Complete information is not yet available.

### **Environmental Effects**

Complete information is not yet available.

### **Fate and Effects in Waste Water Treatment Plants**

Complete information is not yet available.

#### Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

## 13. DISPOSAL CONSIDERATIONS

### **RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal.

## 14. TRANSPORT INFORMATION

### **DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

### **Ocean Shipment (IMDG)**

Not subject to IMDG code.

### **Air Shipment (IATA)**

Not subject to IATA regulations.

## 15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA

**XIAMETER(R) RTV-3010-S CATALYST**

## Inventory of Chemical Substances.

**EPA SARA Title III Chemical Listings****Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

**Section 304 CERCLA Hazardous Substances (40 CFR 302):**

None.

**Section 311/312 Hazard Class (40 CFR 370):**

Acute: No  
Chronic: Yes  
Fire: No  
Pressure: No  
Reactive: No

**Section 313 Toxic Chemicals (40 CFR 372):**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1345-16-0	0.1	C.I. Pigment Blue 28

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

**Supplemental State Compliance Information****California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

**New Jersey**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
63148-62-9	70.0 - 90.0	Polydimethylsiloxane
471-34-1	15.0 - 35.0	Calcium carbonate
68928-76-7	5.0 - 10.0	Dimethylbis[(1-oxoneodecyl)oxy]stannane
7732-18-5	1.0 - 5.0	Water
1345-16-0	<0.1	C.I. Pigment Blue 28

**XIAMETER(R) RTV-3010-S CATALYST**

**Pennsylvania**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
63148-62-9	70.0 - 90.0	Polydimethylsiloxane
471-34-1	15.0 - 35.0	Calcium carbonate
68928-76-7	5.0 - 10.0	Dimethylbis[(1-oxoneodecyl)oxy]stannane

**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

XIAMETER(R) is a trademark of Dow Corning Corporation

<http://www.xiameter.com>