

# MATERIAL SAFETY DATA SHEET

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: CIRCALOK 6702 A
Product Use/Class: ENCAPSULANT, PART A

LORD CORPORATION 111 LORD DRIVE CARY, NC 27511-7923 TRANSPORTATION EMERGENCY: CHEMTREC 24 HR EMERGENCY NO. 800 424-9300 (Outside Continental U.S. 703 527-3887)

NON-TRANSPORTATION EMERGENCY: 814 763-2345

INFORMATION TELEPHONE: 814 868-0924

EFFECTIVE DATE: 04/25/2011

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name    | CAS Number | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-<br>TWA | OSHA PEL-<br>CEILING | Skin |
|------------------|------------|-----------------------|-------------------|--------------------|------------------|----------------------|------|
| Titanium dioxide | 13463-67-7 | 5.0 %                 | 10 mg/m3          | N.E.               | 15 mg/m3         | N.E.                 | N.A. |

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

### 3. HAZARDS IDENTIFICATION

\*\*\* **EMERGENCY OVERVIEW** \*\*\*: Red Liquid, with No odor. May cause skin and eye irritation. This product contains a residual amount of a chemical substance that may cause an allergic skin and/or respiratory reaction.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: No inhalation hazard expected during normal workplace use.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Prolonged or repeated contact may result in dermatitis. IARC has designated titanium dioxide (TiO2) as Group 2B – possibly carcinogenic to humans in dust form. However, a number of long term animal studies and human epidemiology studies evaluating TiO2 and workplace exposure show insufficient evidence for carcinogenic affects. EPA, NTP and OSHA do not designate TiO2 as a carcinogen and ACGIH designates TiO2 as A4 - not classifiable as a human carcinogen. TiO2 is not present in this product as a dust and no airborne exposure is expected during application. This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees F (150 C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and known cancer hazard. Workplace exposure to formaldehyde is regulated by OSHA Standard 29 CFR 1910.1048.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation, Ingestion, Eye Contact

## 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

Product: CIRCALOK 6702 A, Effective Date: 04/25/2011

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Give victim one or two glasses of water or milk. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

## 5. FIRE-FIGHTING MEASURES

FLASH POINT: 201 °F, 93 °C

Setaflash Closed Cup

LOWER EXPLOSIVE LIMIT (%): Not Applicable

UPPER EXPLOSIVE LIMIT (%): Not Applicable

**AUTOIGNITION TEMPERATURE: N.D.** 

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

# 6. ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Use self-contained breathing equipment. Notify appropriate authorities if necessary. Contain and remove with inert absorbent material. Avoid contact. Keep non-essential personnel away from spill area. Before attempting cleanup, refer to hazard caution information in other sections of the MSDS form. Avoid breathing vapors.

## 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Do not weld or flame-cut an empty drum. Use with adequate ventilation.

STORAGE: Store only in well-ventilated areas. Keep from freezing. Keep container closed when not in use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

**RESPIRATORY PROTECTION:** Respiratory protection is not required under normal working conditions where adequate ventilation is present. Note: If the exposure limit for formaldehyde is exceeded, a formaldehyde-specific, formaldehyde/organic vapor combination, or airline respirator may be required.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

Page: 2

Product: CIRCALOK 6702 A, Effective Date: 04/25/2011

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR:NoBOILING RANGE:N.A.APPEARANCE:RedVAPOR PRESSURE:N.D.

PHYSICAL STATE: Liquid VAPOR DENSITY: Not Applicable N.D. Not Applicable **ODOR THRESHOLD: EVAPORATION RATE:** Insoluble 19.02 lb/gal **SOLUBILITY IN H2O: DENSITY, LB/GL:** N.A. 0.62 % **VOLATILE BY WEIGHT:** pH: FREEZE POINT: N.D. **VOLATILE BY VOLUME:** 0.01 %

COEFFICIENT OF WATER/OIL N.D.

**DISTRIBUTION:** 

(See section 16 for abbreviation legend)

# 10. STABILITY AND REACTIVITY

**CONDITIONS TO AVOID:** High temperatures.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

# 11. TOXICOLOGICAL INFORMATION

 PRODUCT LD50
 (ORAL)
 No Data

 (DERMAL)
 No Data

 PRODUCT LC50
 No Data

# 12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

# 14. TRANSPORT INFORMATION

This product is NOT REGULATED for non-bulk road shipments. For the most accurate shipping information, refer to your transportation/compliance department regarding changes in package size, mode of shipment or other regulatory descriptors.

# 15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

Page: 3

Product: CIRCALOK 6702 A, Effective Date: 04/25/2011

This product is considered hazardous as defined by 29 CFR 1910.1200 (OSHA HazCom Standard.)

#### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.

**NONE** 

#### TOXIC SUBSTANCES CONTROL ACT:

#### **INVENTORY STATUS**

The chemical substances in this product are on the TSCA Section 8 Inventory.

#### **EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**NONE** 

# 16. OTHER INFORMATION

HMIS RATINGS - HEALTH: 1\* FLAMMABILITY: 1 PHYSICAL HAZARD: 0

\* - Indicates a chronic hazard: see Section 3

### **VOLATILE ORGANIC COMPOUNDS**

Calculated: 0 lb/gal, 0 g/l

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

# **DISCLAIMER**

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

Page: 4