



Public

Rev:1

Effective: 05/24/99

Status: Active

Woodgrain and Stripe Adhesive Remover

Data Sheet

3M Part No.(s) **3M Part Descriptor(s)**
08908

3M Fax on Demand Identification Number:

Description

This product is designed to remove adhesive residue after the vinyl woodgrain or vinyl stripe has been removed. This product can be applied to baked on paints such as acrylic enamel and base-coat clear-coats.

Features, Advantages, Benefits

Features ⚡Fast removal of adhesive on woodgrain films and stripes.
 ⚡Will not harm cured acrylic enamel or base-coat paints.

Advantages

Benefits

Typical Physical Properties

Container	24 fl. oz. Aerosol Can Contains 22 3/4 fl. oz.
Color	White
Flash Point - °F	Below -50°F
Consistency	Soft Gel
Solvent	Petroleum Distillates and Alcohol
Propellant	Hydrocarbon

Product Uses

Performance Properties

Handling and Application Information

Directions for Use

1. Shake well before using.
2. Apply in shade with the air temperature and can temperature are at least 60°F.
3. Do not apply to surfaces above 90°F.
4. Apply in a criss-cross slow application to adhesive residue.
5. Allow solvent work 1-2 minutes.
6. Wipe adhesive away using a clean soft cloth.

Applications

To remove adhesive residue on baked on paints such as acrylic enamels, base-coat clear-coats etc. caused by the removal of vinyl woodgrain and stripes.

Storage and Handling

Store at room temperature. Rotate stock on a "first-in, first-out" basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 12 months.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

Country

US

This document is public. It may be distributed.

Important Notice to Purchaser

The statements and technical information contained in this technical data sheet are based on tests and data which 3M believes to be reliable, but the accuracy or completeness of such statements and technical information is not guaranteed. **3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application.

* If 'Directions for Use' reference P.N.'s 8984, 8986, or 8987, please read below.

Federal and local air quality regulations may regulate or prohibit the use of surface preparation and cleanup solvents based on VOC content. Consult your local and Federal air quality regulations for information. When using solvents, use in a well ventilated area. Extinguish all sources of ignition in the work area and observe precautionary measures for handling these materials. Refer to product label and MSDS for P.N. 8984, 8986, or 8987 for detailed precautionary information.

LIMITATION OF REMEDIES AND LIABILITY: If the 3M product is proved to be defective, **THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT.**

3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

For Additional Health and Safety Information

See Material Safety Data Sheet (Fax on Demand 1-800-305-0419), or call: **3M Automotive Aftermarket Division** 3M Center, Building 223-6N-01

Phone: 877-MMM-CARS (877-666-2277)

3M Fax on Demand Identification Number

Reference: Goto Ref

Author:

Tonya L. Frisle/IM-IndMktsGp/3M/US

Linda R. Goserud/US-Corporate/3M/US

This is the last page