




## **Multi-Purpose Duct Tape**



Backing:	PE Coated Cloth		
Adhesive:	Rubber		
Liner:	N/A		
Colors:	Silver, Black		
Specifications:		Tested in accordance with UL 723	
Standard Sizes:		48mm x 55m, 72mm x 55m	

## **Applications**

- General repair
- General purpose construction uses
- Bundling, patching, and mending

- Seaming & hanging polyethylene sheeting
- Emergency tape for automotive applications •

Features	Benefits		
<ul> <li>PE-Coated Cloth Backing</li> </ul>	<ul> <li>Conforms well to irregular surfaces</li> </ul>		
	<ul> <li>Resists twisting &amp; curling</li> </ul>		
Natural rubber based adhesive	<ul> <li>High adhesion &amp; holding power for both rough and smooth surfaces</li> </ul>		
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED<sup>®</sup></li> </ul>		

Physical Properties				
	Standard UOM	Metric UOM	Test Method	
Total Thickness	10 mils	254 mic	ASTM D-1000	
Adhesion to Steel	75 oz/in	8.3 N/cm	PSTC-101	
Adhesion to Backing	43 oz/in	4.7 N/cm	PSTC-101	
Tensile Strength	24 lb/in	42 N/cm	ASTM D-1000	
Elongation	21%		ASTM D-1000	
Operating Temperature	40-200°F	4-93°C		
VOC Content	<1 g/L			

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com

Nijverheidsstraat 10 2260 Oevel (Westerlo) Belgium 32-014-722500 Fax 32-014-722570 10/29/13

## Develop Droportion