

tesa® 50124

General Purpose High-Shear Masking Tape

PRODUCT INFORMATION

Product Description

tesa® 50124 is a high-shear creped paper masking tape with a cured rubber-based adhesive. It provides excellent adhesion to a variety of surfaces in a wide range of application fields.

Main Application

- Light Duty Bundling
- Packaging and Closing
- Light Duty Masking
- Non-Critical and Painting Applications

Technical Data

■ Backing material	slightly-creped paper	■ Adhesion to steel	2.9 N/cm
■ Total thickness	140 µm		26.5 oz/in
	5.5 mils	■ Elongation at break	10 %
■ Type of adhesive	natural rubber	■ Tensile strength	35.02 N/cm
			20 lbs/in

For latest information on this product please visit <http://l.tesa.com/?ip=50124>

Page 1 of 1 / As of 09/12/14

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customer@tesatape.com

<http://www.tesatape.com>

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.